

**Report of the High Speed Multimedia Working Group
To the
ARRL Board of Directors
2006 Semiannual Report**

Working Group Members:

Dave Anderson, KG4YZY
Jon Bloom, KE3Z
John Champa, K8OCL - WG Chairman
Gerry Creager, N5JXS - Architect
Joe Cupano, NE2Z - Network Protection
Walt DuBose, K5YFW - Asst Chairman
Steve Ewald, WV1X
Brandon Field, KC8YHE
Rob Flickinger
Alex Fraser, N3NED – Part15 Liaison
Jon Harris, KC8VAB
Stan Horzepa, WA1LOU
Jim Idelson, K1IR
Joe Kasser, G3ZCZ

Jeff King, WB8WKA - Regulatory
Jim Kvochick, WB8AZP
Zack Lau, W1VT – ARRL Lab
Michael Loukides, W1JQ
Robert McGwier, N4HY – SDR WG
Ron Olexa, KA3JIJ
Paul Pescitelli, K4UJ - openHSMM
Project & Webmaster
Paul Rinaldo, W4RI - ARRL CTO
Neil Sablatzky, K8IT – HF Projects
John Stephensen - VHF/UHF Projects
Ned Sterns, AA7A
Carl Stevenson, WK3C
Dave Stubbs, VA3BHF - VPN Projects
Paul Toth, NA4AR
Gene Zimmerman, W3ZZ

Executive Summary

It has been an interesting and exciting time for the HSMM Working Group since our last report to the Board. We have been granted an FCC Experimental License (WC9XLP) to conduct HSMM experiments on the 6M Band. We are using off-set frequency division multiplexed (OFDM) modulation with up to 200 kHz bandwidth signals.

The WG, with support from Chris Imlay, W3KD, and Paul Rinaldo, W4RI, has developed a set of guidelines for the legal use of various computer-to-computer network protection methodologies for use by Radio Amateurs. These guidelines are being reviewed.

Finally, with the July 2006 issue of QST, the WG has gotten its first excellent HSMM-type Product Review conducted by Steve Ford, WB8IMY. It has generated much excellent technical feedback from many radio experimenters across the country.

HSMM Experiments on the 6M Amateur Band

Progress Report on VHF OFDM Modem submitted by John B. Stephensen, KD6OZH

1. Introduction

The purpose of this project is to test wide bandwidth digital transmission for applications such as image transmission in the Amateur Service on its VHF allocations. John B. Stephensen, KD6OZH is doing development and testing, under the auspices of the HSMM Working Group. If this system proves successful, the ARRL may petition the FCC for use of up to 200 kHz bandwidth in the VHF amateur band. The current petition for “regulation by bandwidth” requests 100 kHz maximum bandwidths on the VHF bands.

Current regulations limit bandwidths to 20 kHz on VHF amateur bands so testing is authorized under an FCC Special Temporary Authority (STA) that is effective until September 10, 2006. It authorizes emissions with a bandwidth up to 200 kHz in the band 50.3-50.8 MHz. This frequency range is consistent with both ARRL national voluntary band plans and applicable local band plans in the Fresno, California area where testing will be done. Specifically, in those band plans, the segment 50.3-50.6 MHz is designated for “all modes” and the segment 50.6-50.8 MHz is designated for “nonvoice communications.” The STA authorizes 1.5 kW peak, a 200 kHz maximum bandwidth and 384 kbps maximum data rate.

2. Description

The modem being developed is a modification of the UHF offset frequency division multiplexed (OFDM) modem tested on the 70-cm amateur band. OFDM splits a high-rate data stream into multiple parallel low-rate streams transmitted on multiple subcarriers. As the signal propagates, it is reflected and refracted, giving rise to multiple echoes that corrupt data. OFDM slows the rate so those echoes are confined to small gaps between transmitted symbols. The technology is similar to that used on HF bands, but the data rate of each subcarrier is higher as the maximum path length is considerably shorter.

This modem consists of software written in Verilog, assembly and C language that runs on a DCP-1 card containing a Xilinx XC3S400 field-programmable gate array (FPGA) and Oki Semiconductor ML67Q5003 microcontroller. One DCP-1 attaches to the intermediate frequency (IF) output of a modified ATR-2000 receiver at one end of the link and another attaches to small printed circuit board with a quadrature modulator IC (Atmel U2790) and the power amplifier from the ATR-2000 at the other end of the link. The transmitter is in a fixed location (Lat: 36d 46m 30s N, Lon: 119d 46m 22s W) and can generate 150 WPEP into an 8 dBi gain vertical antenna (Diamond Antenna DP-GH62). The receiver is mobile and uses a Ham-stick antenna mounted on the roof of a SUV.

The DCP-1 and ATR-2000 are documented in articles published in QEX. The UHF OFDM modem specification is on the ARRL web site and a new version, covering VHF operation, of the document will be published as part of this testing. Documentation of the modem hardware and source code will be made available to radio amateurs after testing.

Three data formats will be tested. These are designed for 50, 100 and 200 kHz channels. Initial tests will use 750 Hz subcarrier spacing with an inter-symbol guard interval of 1/8 symbol period. This combination was selected to support relatively small channels and still have a guard interval that allows rejection of inter-symbol interference in any conceivable operating environment. Field testing of ATSC (digital) television systems showed a maximum delay spread of 90 μ s and the resulting guard interval for the VHF OFDM modem is 166 μ s. The resulting system should be able to operate over LOS or NLOS paths in most terrain with directional or omnidirectional antennas. The signal formats use a central pilot carrier and upper and lower sidebands with 24, 48 or 96 data subcarriers plus 2 trellis-terminating subcarriers each. The subcarriers use differential 8-ary phase shift keyed (PSK) modulation with rate 2/3 convolutional coding. The resulting encoded data rates are 96, 192 and 384 kbps with user data rates of 64, 128 and 256 kbps.

3. Progress

Verilog code has been generated for the VHF OFDM modem and 95% of it has been successfully simulated. Simulation has taken longer than expected due to problems associated with IP (intellectual property) upgrades in the Xilinx development software. Modifications to the original UHF modem included:

1. Reducing the size of the finite impulse response (FIR) digital low-pass filters to allow 3 programmable filter stages instead of 2.
2. Increasing filter coefficient precision from 18 to 24 bits.
3. Writing a new encoder and Viterbi decoder to convert from the Ungerboeck trellis-coded modulation (TCM) using a 4-state encoder in the UHF modem to a bit-independent coded modulation (BICM) with 8-states.
4. Modifying the fast Fourier transform (FFT) implementation to support 17-bit data and reduce memory requirements. The FFT multiplexes and demultiplexes the subcarriers.
5. Modifications in multiple modules to allow different numbers of subcarriers.
6. Converting interfaces between circuits using different clock rates from using block RAM (random access memory) in the FPGA to distributed RAM in the FPGA to free block RAM for additional filtering.

The change from TCM to BICM was made to increase performance over fading paths. The TCM scheme was originally designed for additive white Gaussian noise (AWGN) channels as encountered with telephone modems. This will be incorporated into the UHF modem specification. The filtering changes were required to support higher decimation and interpolation rates and provide a better shape factor to limit occupied bandwidth.

Once all the code has been simulated, it will be loaded onto a DCP-1 and the output checked with a spectrum analyzer. Of particular interest is the level of high-order intermodulation distortion (IMD), or splatter, that will be generated in the power amplifier. A signal generator and arbitrary function generator is also available for receiver testing.

The final test will be one-way over-the-air with measurement of bit error rates, allowable SNR (signal to noise ratio) and coverage area. Testing will also be done on the 70-cm band, either before or after the STA expires, to compare coverage areas and amplifier IMD.

HSMM-type Product Review Published in QST

Thanks go to Steve Ford, WB8IMY, Jeff King, WB8WKA, and Paul Pescitelli, K4UJ, for their combined efforts to get an HSMM-type Product Review in the July QST. This is something Neil Sablatzky, K8IT, has advocated for several years. We expect it to help not only the WG mission, but the popularity of QST and the progressive image of the ARRL. Thank you all for your wonderful efforts!

See page 84 of the July 2006 edition of QST for this excellent write-up:

ECLECTIC TECHNOLOGY

The Hinternet and openHSMM

Here are two new words for your Amateur Radio glossary: Hinternet and openHSMM.

The Hinternet refers to High Speed Multimedia (HSMM) Amateur Radio networking. The goal of the Hinternet (and the ARRL HSMM Working Group) is to bring amateur digital communication into the 21st century with RF networks that handle lots of data—everything from text to video—at high speeds.

Hams already share a band with 802.11 wireless networking devices at 2.4 GHz. These are the “Part 15” units that you probably recognize as wireless routers, access points, etc. The difference, however, is that our privileges give us the ability to use more RF output power.

There is very little off-the-shelf ham hardware available for 2.4 GHz, so the Hinternet folks have taken the next logical step: they've turned consumer 802.11 products into amateur transceivers, often at much higher power levels. Unlike your average consumer, hams can connect wireless access points to amplifiers and gain antennas to extend their range from feet to miles. We also know a thing or two about the importance of low-loss transmission lines at microwave frequencies.

To further the Hinternet, openHSMM involves the use of open-source software (such as Linux) to create an enhanced wireless access point appliance. The openHSMM software would utilize the same consumer hardware, but do it in a much more creative way. For instance, to create a scalable network (wired or wireless) it would be beneficial to provide configuration options such as OSPF (Open Shortest Path First). OSPF is a tried and true routing protocol that broadcasts its routes to its neighbors. Using openHSMM, hams can add protocols like OSPF to existing consumer wireless products.

Amateurs have a long history of modifying nonham equipment, and this is just the next chapter in the story. The openHSMM approach could yield big benefits for HSMM emergency networks. Imagine hams quickly setting up such an enhanced network in a disaster area. Information would be flying back and forth at high speeds with automatic dynamic routing as new nodes are brought online or others become unavailable. Hams could travel to various locations, set up HSMM nodes and be sending back vital information in a matter of minutes.

You can learn more about the Hinternet on the Web at www.arrl.org/hsmm, and openHSMM at www.openhsmm.org.

HSMM in the Real World

If you think Amateur Radio HSMM is pie in the sky, think again. HSMM is being put to use in the real world today.

One of the consumer devices that have attracted the most attention among the openHSMM crowd is the Linksys WRT54GL wireless router. There are many of these types of products on the market, but the WRT-54GL is unique because it runs the Linux operating system. This means that you can write your own Linux firmware and upload it to the WRT-54GL, instantly "modifying" it to suit your needs. It is analogous to installing new firmware in an HF transceiver to add new features.

In Hillsdale, Michigan, the Hillsdale CoolCitites, an economic development group, and the Hillsdale Amateur Radio Club have joined forces to establish an HSMM hub using the WRT-54GL. According to Jeff King, WB8WKA, the hub has both consumer and Amateur Radio applications. It provides wireless Internet access for the downtown area (open to all), while hams use it for Field Day and emergency communication exercises. This is a superb example of how amateurs can use their technical expertise to help their communities, and gain substantial benefits in the bargain. The Hillsdale Amateur Radio Club has received some great press about this effort as well.

Could you strike a deal with your town? Would they provide funding, and a nice location, for a wireless access hub that you or your club could install? One that could also be used for specialized ham applications? Think about it.

Steve Ford, WB8IMY . QST Editor . sford@arrl.org July 2006

Respectfully submitted,

Dr. John J, Champa, K8OCL
ARRL Chairman
HSMM Working Group

k8ocl@arrl.net

June 27, 2006